

## Colour chips for decorative surface designing

### Characteristics

HADALAN® ColourChips 89V are light-resistant, coloured decorative chips for making appealing ground coverings.

- Light-resistant
- Colour-fast
- Easy to process

### Use

HADALAN® ColourChips 89V are used in conjunction with the respective HADALAN® coating product for creating decorative surface protection systems for both indoors and outdoors.

### Areas of application:

- Balcony and terrace surfaces
- Floor surfaces, indoors
- Tiling
- Mineral substrates

### Specifications

Packaging	Cardboard boxes
Barrel	1 kg
Colour tones	No. 100 grey/white No. 110 blue/grey No. 120 beige/grey No. 130 yellow/white No. 140 brown/white No. 150 pastel blue/ white
Grain size	2 - 8 mm
Storage	dry, 24 months

### Quantity required

Depending on application	0.08 - 0.3 kg/m <sup>2</sup>
Contrast scattering depending on desired layout	0.05 - 0.15 kg/m <sup>2</sup>
whole-area scattering	0.25 - 0.3 kg/m <sup>2</sup>

## Preparation of the surface

The substrate must have load bearing capacity, be dry on the surface and free of dirt, dust, cleaning agent residues or other separating substances.

In case of significant temperature changes, in conjunction with increased atmospheric humidity, there is a danger of condensate water formation on the surface of the substrate. Before starting the coating work, this water film should have dried completely.

## Application

1. **HADALAN® ColourChips 89V** are scattered in a previously applied adhesive layer while still wet.
2. The scattering for interspersing can be done by hand, or with a scattering cup or a Chiron blower.
3. After complete hardening, a transparent final sealing is required.
4. Further details can be obtained from the respective technical codes of practice or the processing instructions "Renovating, coating and decorative design with HADALAN® PUR liquid plastics.

## hahne system products

HADALAN® PUR Top 32P  
HADALAN® Topcoat M 12P  
HADALAN® PUR Top 32P transparent  
HADALAN® EPV 38L  
HADALAN® VS 12E  
HADALAN® VS-E 12E  
HADALAN® LF41 12E  
HADALAN® LF51 12E

## Important notes

- Follow the processing instructions or the technical codes of practice of the respective system products.
- **HADALAN® ColourChips 89V** should be protected from moisture during the processing. Store dry.

## Ingredients

Polymer colour chips

## Safety provisions/recommendations

No special measures required.

## Disposal

The local waste removal regulations must be observed.

## Manufacturer

Heinrich Hahne GmbH & Co KG  
Heinrich-Hahne-Weg 11  
D-45711 Datteln

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply. Version as of 2.2016